


# TXE-205H

Through hole TCXO  
HCMOS / TTL compatible



**QuartzCom**  
the communications company



## Features

- Applications: mobile communications, instrumentation
- Frequency range up to 200 MHz
- Tight frequency stability vs. temperature
- Low phase noise

Parameter	Specification	
	TXE-205H3	TXE-205H5
Frequency range	1 ~ 200 MHz	
Standard frequencies	8.192, 10.00, 12.80, 13.00, 16.384, 20.00, 25.00, 27.00 & 38.40 MHz	
Frequency stability:		
vs. temperature	≤ ±0.5 ~ ±2.5 ppm	
vs. supply & load change	≤ ±0.2 ppm	±5 %
vs. aging	≤ ±1.0 ppm	1 <sup>st</sup> year
Frequency tolerance ex. factory	≤ ±0.5 ppm	@ +25 °C
Supply voltage	+3.3 V ±5 %	+5.0 V ±5 %
Supply current	10 ~ 40 mA	
Output signal	HCMOS / TTL compatible	
Output level	V <sub>OH</sub> > 0.9 Vdc	V <sub>OL</sub> < 0.1 Vdc
Output load	15 pF / 10 TTL	
Frequency adjustment (optional)	> ±5 ppm	with internal trimmer
Operating temperature range	-30 ~ +75 °C	commercial application
	-40 ~ +85 °C	industrial application
Storage temperature range	-55 ~ +125 °C	
Packaging unit	cardboard box	50 pieces
Customer specifications on request		



## Pin function

- # 1 GND or NC
- # 2 RF Output
- # 3 Vdc Supply
- # 4 GND
- # 5 GND



## Other configuration on request

### Phase noise

@ 20 MHz carrier frequency	-100 dBc/Hz	@	10 Hz
	-130 dBc/Hz	@	100 Hz
	-145 dBc/Hz	@	1 kHz
	-150 dBc/Hz	@	10 kHz
	-155 dBc/Hz	@	100 kHz

## Environmental & Mechanical specification

Shock	MIL-STD-883C, Method 2002, Con B
Vibration	MIL-STD-883C, Method 2007, Con A
Solderability	MIL-STD-883C, Method 2003
Seal integrity	MIL-STD-883C, Method 2014, Con C&A2

2002/95/EC RoHS compliant

08 Jun. 12